

19 Inch 1U Rack CWDM/OADM

Features:

- Low Insertion Loss
- Wide pass band
- High Channel Isolation
- High Stability and reliability



Applications:

- Line Monitoring (CWDM Add/Drop)
- WDM Network
- Fiber Optical amplifier

Performance Specification:

Parameter	4 Channel		8 Channel		16 Channel		
	Mux	Demux	Mux	Demux	Mux	Demux	
Channel Wavelength(nm)	1270~1610						
Center wavelength Accuracy(nm)	±0.5						
Channel Spacing (nm)	20						
Channel Passband(@-0.5dB bandwidth (nm))	>13						
Insertion Loss(dB)	≤1.6		≤2.5		≤3.5		
Channel Uniformity(dB)	≤0.6		≤1.0		≤1.5		
Channel Ripple(dB)	0.3						
Isolation (dB)	Adjacent	N/A	>30	N/A	>30	N/A	>30
	Non-adjacent	N/A	>40	N/A	>40	N/A	>40
Insertion Loss Temperature Sensitivity(dB/°C)	<0.005						
Wavelength Temperature Shifting(nm/°C)	<0.002						
Polarization Dependent Loss(dB)	<0.1						
Polarization Mode Dispersion(PS)	<0.1						
Directivity(dB)	>50						
Return Loss(dB)	>45						
Maximum Power Handling(mW)	500						

Operating Temperature(°C)	-5~+75
Storage Temperature(°C)	-40~85
Package dimension(mm)	19 1U Rack

Remarks: Above specification are for device without connector

Order Information:

Configuration	Channel No.	Channel	Pigtail Type	Fiber length	Dimensio (mm)	Connector
M=Mux D=Demux	04=4 Channel 08=8 Channel 16=16 Channel N=N Channel	27=1270nm 47=1470nm 49=1490nm 61=1610nm SS=special...	0=250um 1=900um 2=2.0mm 3=3.0mm	1=1m 2=1.5m 3=others	1= L100 x W80 xH10 2=L140xW100xH15 3=19 1U Rack	0=None 1=FC/APC 2=FC/PC 3=SC/APC 4=SC/PC 5=others