

RADWIN

2.5Gbps 35W DC POE

Data Sheet



RW-9921-2069

Product Description

- » Extended temperature DC POE device
- » Supports most of RADWIN product portfolio
- » Up to 2.5Gbps Ethernet interface
- » 35 Watts POE power

Product Highlights

- » Carrier class DC POE injector
- » Wide 10-60V DC input range
- » Rated power up to 35W
- » Efficiency >85%
- » Overload, over-voltage and short circuit output protection

Product Specifications:

Output

DC Output Voltage	55VDC
POE scheme	2-pair passive POE (positive wires: 4,5, negative wires: 7,8)
DC Current per wire pair	0.63A@35W
Efficiency	>85%
Rated Power	35W
LED Status Indicator	POE output status

Input

Voltage Range	10-60VDC
Inrush current	80A@cold start
DC connector	Terminal Block (3 pins: +, -, ground)
Wire diameter	up to 16 AWG

Protections

Output Over voltage	Supported
Output Short circuit	Supported
Output Overload	Supported

Environmental

Operating Temperature	-40°C to +70°C / -40°F to 158°F
Humidity	0% to 95% RH

Other

Dimension	160*63*33mm / 6.3*2.5*1.3" (L*W*H)
Weight	245g

Regulatory compliance:

Safety

Safety Standards	UL60950-1, IEC60950-1
------------------	-----------------------

EMC


Emission	FCC part 15B Class B, CISPR-Class B, EN550022 Class B, EN55024, EN61000-3-2, EN61000-3-3, IEC61000-4-2, IEC61000-4-6, IEC61000-4-8, IEC61000-4-11
----------	---

Other

MTBF	261khrs Telcordia SR-332 Issue2
------	---------------------------------

Mechanical drawing:

Measurements in mm



Label:

