

Parameter	C5x	C6x LE	C6x	B6x
Technology	802.11ac OFDM	802.11ax OFDMA	802.11ax OFDMA	802.11ax OFDMA
Antenna	<i>X series Twist On</i> (8/12/20/25/30 dBi)	<i>X series Twist On</i> (8/12/20/25/30 dBi)	<i>X series Twist On</i> (8/12/20/25/30 dBi)	<i>X series Twist On</i> (8/12/20/25/30 dBi)
Built-in GPS	No	No	No	Yes
Channel Width (MHz)	20/40/80	20/40/80	20/40/80/160	Single or Dual 20/40/80/160
Frequencies	4.9-6.4 GHz	5.1-6.4 GHz	5.1-6.4 GHz	5.1-6.4 GHz
Streams/Rate	2/256 QAM	2/1024 QAM	2/1024 QAM	4/1024 QAM
TX Power	27 dBm	27 dBm	27 dBm	27 dBm
Power Consumption	12.9W	20W	20W	30W
IP Rating	IP 67	IP 67	IP 67	IP 67
Interfaces	1xGE	1xGE	1xGE	1xGE, DC Port, 2 x SFP+
Speed (IP Throughput)	730 Mbps	1 Gbps	2 Gbps	3 Gbps
Weight	0.37 Kg	0.7 Kg	0.7 Kg	1.7 Kg
Power Method	Passive PoE (24-56VDC)	Passive PoE (24 VDC)	Passive PoE (24 VDC)	DC, Passive PoE (48-56 V)
Product Picture				

N5-X Modular, Twist-On Antennas

